


Mobile Field Controller





- Windows Mobile® 6.5
- 624MHz Intel X-Scale Processor and Graphics Accelerator
- Integrated *Bluetooth®*, Wi-Fi, and Cellular Modem
- Integrated 5 Megapixel Camera
- VGA Color Display, Sunlight-readable Transflective Touch Screen
- Waterproof IP65



SPECIFICATIONS

System	
CPU	624MHz Intel X-Scale processor and Graphics Accelerator
OS	Microsoft Windows Mobile® 6.5
Memory	256MB NAND Flash MicroSD Card Slot
Display	Sunlight-readable 3.7" VGA (480 x 640) transflective touch screen
Communications	Wireless LAN 802.11 b/g Bluetooth® USB Type Mini-B
Integrated Sensors	"

GPS Type 12 channel SIRFstar III chipset
Horizontal Accuracy 2-5 m

Built-in Camera 5 MP, Autofocus Camera

Environmental

Water Protection IP65

Operating Temperature -4°F to 140°F (-20°C to 60°C)

Storage Temperature -22°F to 158°F (-30°C to 70°C)

Drop Test Drop 3.3′ (1 m)

Physical

Dimensions 3.7" x 6.3" x 1.2" (w x h x d) 94 x 160 x 30.5 mm

Weight with Battery 9.6 oz (272 g)

Battery 3000 mAh Li-lon battery

Operating Time Up to 10 hours of operation

For more specification information: topconpositioning.com/s-10

Topcon TotalCare

This online resource comes with real live people ready to help. Get expert training from Topcon University's large collection of online materials, and expert help directly from Topcon Technical Support.

Access software and firmware updates, current publications, and guidance from the experts at Topcon all right from your computer or mobile device.

Please visit the TotalCare website to learn more. topcontotalcare.com



7400 National Drive • Livermore • CA 94550 (925) 245-8300

Specifications subject to change without notice. ©2014 Topcon Corporation All rights reserved. P/N: 7010-2163 Rev. A TF 10/14

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

PRIMARY FEATURES

S-10

An entry-level field controller that has high performance in a compact design that delivers results with the Topcon MAGNET software family



Rugged

The S-10 is a handheld controller that is waterproof (IP65) with an integrated cell modem and *Bluetooth*® allowing the user to easily connect to GNSS receivers cable free for network correction or MAGNET Relay.

Long Life Battery

The 3000 mAh Li-lon battery provides up to 10 hours to your extended working day.

Easy, Intuitive Operation

Windows Mobile® 6.5 operating system and the 3.7" sunlight readable display with MAGNET Field is simple to operate.

Integrated Sensors

The 12 channel GPS provides a 2-5 meter solution for locations in the field to tag Geo locations for pictures recorded with the 5 MP camera.

KIT COMPONENTS



Standard Configuration

- S-10 Controller
- Handstrap
- Stylus
- USB cable and charger
- Quick Start Guide
- Battery

Optional Accessories

Pole Bracket

Your local Authorized Topcon dealer is: